





EUROCORD®

FLOSTER PARA/HD PARA BIONDA



STOCK				
	mm	mm	mt	kg/mt
•	50x58	4	12	0,71
•	60x68	4	12	0,84
•	70x78	4	12	0,98
	80x88	4	12	1,10
•	90x98	4	12	0,90
•	102x110	4	12	1,33
•	120x128	4	12	1,57
	130x138	4	12	1,69
•	140x148	4	12	1,82
•	152x160	4	12	1,96
•	168x176	4	12	2,16
•	193x201	4	9	2,48
•	200x208	4	12	2,56
•	220x228	4	6	2,81
•	254x262	4	12	3,24
•	273x281	4	10	3,47
•	305x313	4	12	3,90
•	323x331	4	6	4,14
•	350x358	4	6	4,45
•	400x408	4	7	5,10
•	500x508	4	6	6,19



IMPIEGO

Manichetta in gomma utilizzata per convogliare il materiale sfuso all'uscita della tramoggia (sabbia, cemento, ghiaia, cereali);



STRUTTURA

Tubo prodotto su mandrino in solgomma monostrato.

MATERIALE: Gomma NR (natural rubber)

SUPERFICIE: liscia ad impressione tela

DUREZZA: 45 shore a ± 5

CARICO DI ROTTURA: 150 Kg/cm²

ALLUNGAMENTO A ROTTURA: 500%

CONFEZIONAMENTO

rotoli tagliati a misura

NORME

ISO 1307



TEMPERATURA

-40°C / +70°C

-40°F / +158°F